

UK DECLARATION OF PERFORMANCE

Declaration of Performance No: PB-YSHG-100821/00_UKCA

1. Identification of Product: Dry pressed ceramic floor tile, $3,0 \% \leq E_b \leq 6,0 \%$ Group BIIa GL.

2. Intended Use(s): For internal floorings

3. Name and contact address of manufacturer:

Yurtbay Seramik Oklubalı Mh. PK:22 26670 Inonu Eskisehir/Turkey

Tel: +90 222 596 62 00 Fax: +90 222 596 61 99 www.yurtbayseramik.com info@yurtbay.com

4. Sytem or systems of assesment and verification of constancy of performance of the construction product: System 4

According to the Construction Products (amendment etc.) (EU Exit) Regulations 2020 [(EU) No:305/2011] the product group which reference number is given above confirm all the requirements of BS EN 14411:2016 standard for ceramic tiles.

5. Declared Performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1fl	(not required)
Resistance to fire	Fireproof	
External fire performance	NPD	
Noise absorption	NPD	
Emissions of dangerous substances	NPD	
Release of dangerous substance, for	NPD	BS EN 14411:2016
-Cadmium		
-Lead		
Breaking Strength	Thickness $\geq 7,5$ mm. min. S:1000 N Thickness $< 7,5$ mm. min. S:600 N	
Slipperiness	Antislip products are defined on the package	
Tactility	NPD	
Bond Strength/adhesion for:		
Cementitious adhesive, type C2	Min. 1 N/mm ²	
Thermal shock resistance	Pass	
Durability for:		
-Internal use:	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 5. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

GENERAL MANAGER

Köksal ÇINAR

10 th of August, 2021

YURT BAY
SERAMİK SANAYİ VE TİCARET A.Ş.