

DECLARATION OF PERFORMANCE

Declaration of Performance No: PB-YSYK-100821/00_UKCA

1. Identification of Product: Dry pressed ceramic floor tiles, water absorption, $0,5 \% \leq E_b \leq 3,0 \%$, Group BIb GL – Ek H

2. Intended Use(s): For used as floor and wall covering in interior spaces.

3. Manufacturer:

Yurtbay Seramik San. ve Tic. A.Ş.

Oklubalı Mh. No:22 26670 İnönü Eskisehir/TÜRKİYE

Tel: +90 222 596 62 00

Fax: +90 222 596 61 99

www.yurtbayseramik.com

info@yurtbayseramik.com

4. Authorized Representative: Yurtbay Seramik San. ve Tic. A.Ş

5. System(s) for evaluating and verifying constancy of performance: System 4

6. Harmonized Standard: BS EN 14411:2016

7. Declared Performance:

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to Fire	A1FL	BS EN 14411:2016
Breaking Strength	Thickness ≥ 7.5 mm ≥ 1100 N Thickness < 7.5 mm ≥ 700 N	
Flexural Strength	≥ 30 N/mm ²	
Release of Dangerous Substance	Company Declared Value	
-Cadmium	$\leq 0,03$ mg/dm ² Cd	
-Lead	$\leq 0,2$ mg/dm ² Pb	
Thermal Shock Resistance	Pass	
Slipperiness	NPD	
Bond Strength/Adhesion		
Cementitious adhesive, type C2	Min. 1,0 N/mm ²	
Durability		
- Internal use:	Pass	

According to the Construction Products (amendment etc.) (EU Exit) Regulations 2020 [(EU) No:305/2011] the product group which reference number is given above confirm all the requirements of BS EN 14411:2016 standard for ceramic tiles.

Signed for and on behalf of the manufacturer by:

**YURT BAY SERAMİK**
SANAYİ ve TİC. A.Ş.
A.Cengiz ALAN

Quality Assurance Director
İnönü/Eskişehir, 08.02.2024

