

UK DECLARATION OF PERFORMANCE

Declaration of Performance No: PB-YSGK-100821/00_UKCA

- 1. Identification of Product:** Dry pressed ceramic floor tile, Eb $\leq 0,5$ % Group BIa GL, UGL – Ek G
- 2. Intended Use(s):** For used as floor and wall covering in interior and exterior spaces.
- 3. Manufacturer:**
Yurtbay Seramik San. ve Tic. A.Ş.
Okulbalı Mh. No:22 26670 İnönü Eskisehir/TÜRKİYE
Tel: +90 222 596 62 00 Fax:+90 222 596 61 99
www.yurtbayseramik.com info@yurtbayseramik.com
- 4. Authorized Representative:** Yurtbay Seramik San. ve Tic. A.Ş
- 5. System(s) for evaluating and verifying constancy of performance:** System 4
- 6. Harmonized Standard:** BS EN 14411:2016

7. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to Fire	A1FL	BS EN 14411:2016
Breaking Strength	Thickness ≥ 7.5 mm. ≥ 1300 N Thickness < 7.5 mm. ≥ 700 N	
Flexural Strength	≥ 35 N/mm ²	
Release of Dangerous Substance	Company Declared Value	
-Cadmium	$\leq 0,03$ mg/dm ² Cd	
-Lead	$\leq 0,2$ mg/dm ² Pb	
Thermal Shock Resistance	Pass	
Slipperiness	NPD	
Bond Strength/Adhesion		
Cementitious adhesive, type C2	Min. 1 N/mm ²	
Durability		
-Internal Use:	Pass	
-External Use: Freze-Thaw Resistance	Pass	

According to the Construction Products (amendment etc.) (EU Exit) Regulations 2020 [(EU) No:305/2011] the product group which reference number is given above confirm all the requirements of BS EN 14411:2016 standard for ceramic tiles.

Signed for and on behalf of the manufacturer by:

 **YURTBAY SERAMİK**
SANAYİ ve TİC. A.Ş.

A.Cengiz ALAN

Quality Assurance Director

İnönü/Eskisehir, 08.02.2024

